

PAT-NO: JP407268300A

DOCUMENT-IDENTIFIER: JP 07268300 A

TITLE: ADHESIVE

PUBN-DATE: October 17, 1995

INVENTOR-INFORMATION:

NAME

ASAI, DAIJIRO

TOMONO, HITOSHI

INT-CL (IPC): C09J131/04, C09J131/04 , C08F218/04 , C09J129/04 , C09J129/12  
, C09J131/02

ABSTRACT:

PURPOSE: To obtain an adhesive excellent in water resistance by mixing a specified aqueous polyvinyl alcohol solution with an ethylene/vinyl acetate copolymer emulsion in such amounts as to give an acetoacetyl group content in a specified range.

CONSTITUTION: An aqueous emulsion containing 1-20 pts.wt. (in terms of the solid matter) aqueous polyvinyl alcohol solution (A) and a copolymer (B) containing repeating units of ethylene and repeating units of a vinyl ester in an ethylene unit to vinyl ester unit weight ratio of (5-70)/100 is prepared. An adhesive based on the formed emulsion and containing 0.1-10 pts.wt. acetoacetyl groups per 100 pts.wt. solid matter is produced. To introduce acetoacetyl groups into the adhesive, acetoacetylated polyvinyl alcohol is used as component A or an acetoacetylated monomer such as vinyl acetoacetate is used as one monomer of the comonomers constituting component B.

COPYRIGHT: (C)1995,JPO

----- KWIC -----

Abstract Text - FPAR (1):

PURPOSE: To obtain an adhesive excellent in water resistance by mixing a specified aqueous polyvinyl alcohol solution with an ethylene/vinyl acetate copolymer emulsion in such amounts as to give an acetoacetyl group content in a specified range.